Stazione di lavaggio

• Consente il lavaggio e il flussaggio di impianti anche di grandi dimensioni.
• elimina tutti i residui solidi causati dalla rottura del compressore o del filtro
• rimuove completamente i residui di olio dal sistema HVAC e A/C

Prerogative:
• Lavaggio di circuiti di volume anche superiore ai 10 lt standard della tanica
• Attacco per tanica supplementare
• Attacco per bombola azoto esterna
• Rubinetti esterni e adesivo sinottico per facilitare le operazioni
• Pompa dotata di tenuta meccanica e guarnizioni in PTFE
• Filtro meccanico in aspirazione
• Tubi flessibili con:
- Attacchi intercambiabili da 1/4"SAE, 3/8"SAE e 1/2"SAE per HVAC
- Coni universali per A/C (settore auto)

Flushing station

• Allow the flushing and the fluxing of systems even of big dimensions.
• remove all solid residues caused by the breakage of the compressor or of the filter
• remove completely the residues of oil from the HVAC and A/Csystems

Properties:
• Flushing of circuit that have a bigger volume than the 10 standard litres of the container
• Preset connection for extra container
• Connection for external nitrogen bottle
• External valves and synoptic label for easy operations
• Pump equipped with mechanical seal and PTFE gaskets
• A mechanical filter on the suction side
• Flexible hoses with:
- Interchangeable connections of 1/4"SAE, 3/8"SAE and 1/2"SAE for HVAC
- Universal cones for A/C (automotive)

Caratteristiche tecniche
Technical features

Portata pompa Pump flow rate	14 l/min
Pressione max pompa Pump max pressure	0,45 MPa
Potenza motore pompa Pump motor power	0,6kW
Alimentazione Power supply	230-240/1/50-60 Hz
Dimensioni Dimensions	300x220x550mm
Peso Weight	13 kg

Codice Code	Modello Model	Adatto per Suitable for
13005037001	FLUSH 1-PLUS-HVAC	Sistemi HVAC HVAC systems
13005038001	FLUSH 1-PLUS-A/C	Sistemi A/C (settore auto) A/C systems (automotive)

Utilizzabile con fluido di lavaggio SUPER FLUSH
To be used with SUPER FLUSH flushing fluid

Ricambi e accessori
Spare parts and accessories

Valvole a sfera con tenute in PTFE, adatte per utilizzo con SUPER-FLUSH, e giunti per la realizzazione di valvole di deviazione.

Codice Code	Modello Model	Descrizione Description
05003017		Valvola a sfera 1/4"GAS f x 1/4"GAS f con tenute in teflon Ball valve 1/4"GAS f x 1/4"GAS f with Teflon seals
05052011	48F4	Giunti diritti 1/4"SAE m X 1/4NPT m Male unions
05052012	48F6	Giunti diritti 3/8"SAE m X 1/4NPT m Male unions
05052034	U1-8B	Giunti diritti 1/2"SAE m X 1/4NPT m Male unions

Ball valves with PTFE seals, suitable to be used with SUPER-FLUSH, and male unions to create deflection valves.

Codice Code	Modello Model	Descrizione Description
02041003	F1-PUMP	Pompa per FLUSH1 - FLUSH1 pump
14015027	F1-CART	Cartuccia per filtro meccanico Cartridge for mechanical filter