





**Tecumseh**

<b>SILAG2516Z-TZ</b>	<b>Tension TZ : 400V 3~ 50Hz / 440V 3~ 60 Hz</b>
----------------------	--

Les performances sont données dans les <b>conditions EN13215</b> :	Gaz aspirés :	20.0 °C
Condition Dew	Sous refroidissement :	3.0 K
The performance data are in <b>EN13215 conditions</b> :	Return gas :	20.0 °C
Dew Condition	Subcooling :	3.0 K

<b>50 Hz R452A</b>									
<b>N°6686</b>									
5   T ambience	6   T évaporation	(°C)	<b>-40</b>	<b>-35</b>	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	1605	2410	3351	4419	5598	6867	8212
	2   P absorbée	(W)	1410	1739	2090	2473	2896	3368	3894
	3   I absorbée	(A)	3.82	4.13	4.53	5.03	5.60	6.24	6.92
	4   Tc	(°C)	27.0	27.9	29.4	31.6	34.2	37.1	40.3
<b>32</b>	1   P frigorifique	(Watt)	1236	1970	2823	3788	4855	6012	7251
	2   P absorbée	(W)	1335	1691	2066	2470	2912	3397	3934
	3   I absorbée	(A)	3.72	4.07	4.51	5.03	5.63	6.29	6.99
	4   Tc	(°C)	33.8	34.5	35.9	37.8	40.2	42.9	45.7
<b>43</b>	1   P frigorifique	(Watt)	688	1302	2010	2813	3707	4691	5775
	2   P absorbée	(W)	1164	1562	1977	2416	2888	3400	3958
	3   I absorbée	(A)	3.54	3.93	4.41	4.97	5.60	6.28	7.00
	4   Tc	(°C)	44.5	45.0	46.0	47.7	49.6	51.9	54.3

<b>60 Hz R452A</b>									
<b>N°6686</b>									
5   T ambience	6   T évaporation	(°C)	<b>-40</b>	<b>-35</b>	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	1666	2639	3723	4911	6192	7557	9000
	2   P absorbée	(W)	1486	1907	2336	2794	3295	3855	4486
	3   I absorbée	(A)	3.35	3.80	4.28	4.80	5.39	6.07	6.86
	4   Tc	(°C)	32.0	32.7	34.1	36.1	38.6	41.5	44.5
<b>32</b>	1   P frigorifique	(Watt)	1148	2053	3056	4152	5335	6601	7952
	2   P absorbée	(W)	1281	1758	2236	2735	3272	3861	4517
	3   I absorbée	(A)	3.13	3.64	4.16	4.73	5.36	6.08	6.90
	4   Tc	(°C)	39.1	39.7	40.9	42.7	45.0	47.6	50.3
<b>43</b>	1   P frigorifique	(Watt)		1141	2003	2946	3972	5086	6314
	2   P absorbée	(W)		1371	1943	2524	3134	3787	4496
	3   I absorbée	(A)		3.20	3.83	4.48	5.20	5.99	6.88
	4   Tc	(°C)		50.7	51.7	53.2	55.0	57.2	59.4

1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = ambient temperature 6 = evaporating temperature

Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.

Note : Tecumseh reserves the right to change information contained in this document without notification.

© 2022 Tecumseh Products Company  
All rights reserved



**Tecumseh**

<b>SILAG2516Z-TZ</b>	<b>Tension TZ : 400V 3~ 50Hz / 440V 3~ 60 Hz</b>
----------------------	--

Les performances sont données dans les <b>conditions EN13215</b> :	Gaz aspirés :	20.0 °C
Condition Dew	Sous refroidissement :	3.0 K
The performance data are in <b>EN13215 conditions</b> :	Return gas :	20.0 °C
Dew Condition	Subcooling :	3.0 K

<b>50 Hz R404A</b>									
<b>N°6681</b>									
5   T ambience	6   T évaporation	(°C)	<b>-40</b>	<b>-35</b>	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	1878	2705	3678	4781	5990	7275	8598
	2   P absorbée	(W)	1519	1868	2241	2642	3080	3561	4094
	3   I absorbée	(A)	4.22	4.48	4.86	5.36	5.99	6.75	7.67
	4   Tc	(°C)	28.4	30.1	32.1	34.3	36.9	39.7	42.8
<b>32</b>	1   P frigorifique	(Watt)	1477	2225	3100	4091	5179	6342	7552
	2   P absorbée	(W)	1462	1831	2224	2646	3102	3600	4146
	3   I absorbée	(A)	4.10	4.41	4.84	5.39	6.06	6.87	7.81
	4   Tc	(°C)	35.2	36.7	38.5	40.6	42.9	45.5	48.2
<b>43</b>	1   P frigorifique	(Watt)	875	1497	2217	3031	3931	4905	5941
	2   P absorbée	(W)	1317	1719	2146	2602	3092	3620	4192
	3   I absorbée	(A)	3.87	4.27	4.79	5.42	6.17	7.04	8.04
	4   Tc	(°C)	45.8	47.1	48.7	50.4	52.4	54.5	56.7

<b>60 Hz R404A</b>									
<b>N°6681</b>									
5   T ambience	6   T évaporation	(°C)	<b>-40</b>	<b>-35</b>	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	2002	2980	4089	5311	6620	7988	9382
	2   P absorbée	(W)	1644	2068	2515	2993	3513	4087	4725
	3   I absorbée	(A)	3.61	4.06	4.55	5.09	5.70	6.40	7.20
	4   Tc	(°C)	33.3	34.8	36.7	38.8	41.2	43.9	46.9
<b>32</b>	1   P frigorifique	(Watt)	1430	2335	3357	4479	5681	6939	8229
	2   P absorbée	(W)	1455	1930	2422	2942	3500	4104	4768
	3   I absorbée	(A)	3.41	3.91	4.45	5.03	5.69	6.42	7.25
	4   Tc	(°C)	40.3	41.7	43.4	45.4	47.6	50.0	52.6
<b>43</b>	1   P frigorifique	(Watt)	570	1345	2216	3172	4199	5284	6419
	2   P absorbée	(W)	988	1555	2137	2741	3374	4045	4763
	3   I absorbée	(A)	2.92	3.50	4.13	4.81	5.54	6.35	7.25
	4   Tc	(°C)	51.4	52.6	54.0	55.7	57.5	59.5	61.6

1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = ambient temperature 6 = evaporating temperature

Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.  
 Note : Tecumseh reserves the right to change information contained in this document without notification.

© 2022 Tecumseh Products Company  
All rights reserved



**Tecumseh**

<b>SILAG2516Z-TZ</b>	<b>Tension TZ : 400V 3~ 50Hz / 440V 3~ 60 Hz</b>
----------------------	--

Les performances sont données dans les <b>conditions EN13215</b> :	Gaz aspirés :	20.0 °C
Condition Dew	Sous refroidissement :	3.0 K
The performance data are in <b>EN13215 conditions</b> :	Return gas :	20.0 °C
Dew Condition	Subcooling :	3.0 K

<b>50 Hz R448A (*)</b>							
							<b>N°7054</b>
5   T ambience	6   T évaporation	(°C)	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	2760	3806	5020	6380	7854
	2   P absorbée	(W)	1967	2346	2755	3203	3697
	3   I absorbée	(A)	4.31	4.80	5.36	5.96	6.61
	4   Tc	(°C)	30.7	32.5	34.7	37.2	40.1
<b>32</b>	1   P frigorifique	(Watt)	2307	3249	4353	5603	6973
	2   P absorbée	(W)	1949	2348	2776	3240	3748
	3   I absorbée	(A)	4.30	4.82	5.40	6.03	6.69
	4   Tc	(°C)	37.3	39.0	41.0	43.2	45.8
<b>43</b>	1   P frigorifique	(Watt)	1642	2428	3364	4445	5659
	2   P absorbée	(W)	1866	2302	2766	3262	3797
	3   I absorbée	(A)	4.21	4.77	5.39	6.05	6.74
	4   Tc	(°C)	47.7	49.2	50.9	52.8	54.9

<b>60 Hz R448A (*)</b>							
							<b>N°7054</b>
5   T ambience	6   T évaporation	(°C)	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	3050	4237	5588	7082	8688
	2   P absorbée	(W)	2186	2645	3137	3674	4268
	3   I absorbée	(A)	4.05	4.58	5.16	5.82	6.56
	4   Tc	(°C)	35.4	37.2	39.2	41.5	44.3
<b>32</b>	1   P frigorifique	(Watt)	2480	3575	4832	6234	7758
	2   P absorbée	(W)	2086	2589	3121	3691	4311
	3   I absorbée	(A)	3.95	4.52	5.15	5.84	6.62
	4   Tc	(°C)	42.4	44.0	45.8	47.9	50.4
<b>43</b>	1   P frigorifique	(Watt)		2585	3696		
	2   P absorbée	(W)		2376	2988		
	3   I absorbée	(A)		4.28	5.00		
	4   Tc	(°C)		54.7	56.3		

**1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = ambient temperature 6 = evaporating temperature**

(\*) Veuillez vous référer strictement aux Recommandations d'Utilisation et Bulletins Marketing Tecumseh du fait de la température de refoulement élevée pour les applications LBP.  
 (\*) Due to very high discharge temperature especially on LBP conditions, please strictly refer to Tecumseh Guidelines & Marketing Bulletin when using this refrigerant.

**Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.**

**Note : Tecumseh reserves the right to change information contained in this document without notification.**

© 2022 Tecumseh Products Company  
All rights reserved



**Tecumseh**

<b>SILAG2516Z-TZ</b>	<b>Tension TZ : 400V 3~ 50Hz / 440V 3~ 60 Hz</b>
----------------------	--

Les performances sont données dans les <b>conditions EN13215</b> :	Gaz aspirés :	20.0 °C
Condition Dew	Sous refroidissement :	3.0 K
The performance data are in <b>EN13215 conditions</b> :	Return gas :	20.0 °C
Dew Condition	Subcooling :	3.0 K

<b>50 Hz R449A (*)</b>							
							<b>N°6827</b>
5   T ambience	6   T évaporation	(°C)	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	2761	3808	5022	6384	7858
	2   P absorbée	(W)	1967	2346	2755	3203	3697
	3   I absorbée	(A)	4.31	4.80	5.36	5.96	6.61
	4   Tc	(°C)	30.7	32.5	34.7	37.2	40.0
<b>32</b>	1   P frigorifique	(Watt)	2308	3251	4355	5606	6977
	2   P absorbée	(W)	1949	2348	2776	3240	3748
	3   I absorbée	(A)	4.30	4.82	5.40	6.03	6.69
	4   Tc	(°C)	37.3	39.0	41.0	43.2	45.8
<b>43</b>	1   P frigorifique	(Watt)	1643	2429	3365	4447	5662
	2   P absorbée	(W)	1866	2302	2766	3262	3797
	3   I absorbée	(A)	4.21	4.77	5.39	6.05	6.74
	4   Tc	(°C)	47.7	49.2	50.8	52.7	54.9

<b>60 Hz R449A (*)</b>							
							<b>N°6827</b>
5   T ambience	6   T évaporation	(°C)	<b>-30</b>	<b>-25</b>	<b>-20</b>	<b>-15</b>	<b>-10</b>
<b>25</b>	1   P frigorifique	(Watt)	3052	4240	5591	7086	8693
	2   P absorbée	(W)	2186	2645	3137	3674	4268
	3   I absorbée	(A)	4.05	4.58	5.16	5.82	6.56
	4   Tc	(°C)	35.4	37.2	39.2	41.5	44.3
<b>32</b>	1   P frigorifique	(Watt)	2482	3577	4835	6238	7763
	2   P absorbée	(W)	2086	2589	3121	3691	4311
	3   I absorbée	(A)	3.95	4.52	5.15	5.84	6.62
	4   Tc	(°C)	42.4	44.0	45.8	47.9	50.4
<b>43</b>	1   P frigorifique	(Watt)		2586	3697		
	2   P absorbée	(W)		2376	2988		
	3   I absorbée	(A)		4.28	5.00		
	4   Tc	(°C)		54.7	56.2		

**1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = ambient temperature 6 = evaporating temperature**

(\*) Veuillez vous référer strictement aux Recommandations d'Utilisation et Bulletins Marketing Tecumseh du fait de la température de refoulement élevée pour les applications LBP.  
 (\*) Due to very high discharge temperature especially on LBP conditions, please strictly refer to Tecumseh Guidelines & Marketing Bulletin when using this refrigerant.

**Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.**

**Note : Tecumseh reserves the right to change information contained in this document without notification.**

© 2022 Tecumseh Products Company  
All rights reserved